

EAGLE™ PACK 240

X-RAY INSPECTION SYSTEM



Beam Width	Package Height
162mm (6.4")	101mm (4")
182mm (7.2")	76mm (3")
202mm (7.9")	50mm (2")
222mm (8.7")	25mm (1")
242mm (9.5")	BELT

Feature Highlights

- **Advanced image analysis with proprietary SimulTask™ software for automatic detection and rejection**
- **Auto-learn enables simple setup for new products**
- **Built in modem and Ethernet card for remote technical support**
- **High speed imaging up to 120MPM [400FPM]**
- **A/C Cooling is standard on all models**
- **HACCP ready, full event and contaminant logging**

The Smiths Detection Eagle line of inspection systems provides product inspection of foreign contaminants including: metal, stone, glass, dense plastics and calcified bone. The systems can also check weigh, measure fill-level, verify component presence/absence and are multi-lane capable; Smiths can help maximize your overall line efficiency.

The Eagle Pack 240 is designed for inspection of high-speed flow-wrap lines, blister packs and small packaged items. The system provides 240mm [9.4"] of detection coverage at the belt, is capable of high-speed imaging up to 120MPM [400FPM] with multiple inspection capabilities for

line rates up to 1000PPM. Standard and high-resolution packages are available to satisfy each customer's specific requirements by balancing smaller contaminant detection and high line speeds.

All Eagle systems are network capable, allowing remote access by Smiths Detection's expert technicians to quickly diagnose and often correct issues without dispatching a technician for on-site service. The system is constructed using 304 stainless steel to a durable IP65 environmental rating to suit any packaging plant environment.

Technical Data **EAGLE PACK 240**

General Specifications

Max. object size	See beam geometry
Conveyor heights	635mm to 1219mm +/-50mm [25" to 48" +/-2"]
Conveyor lengths	1321mm [4'4"], 1626mm [5'4"], 1930mm [6'4"]
Conveyor speed at mains frequency	15 to 120MPM [50 to 400FPM]

X-ray Generator

Max. anode voltage • cooling	0-70kV • hermetically sealed oil bath
Current	1mA/2mA
Beam direction	Top center, directed down

Image Generating System

Software	Simul-Task proprietary image processing software
Computer	Industrial PC Intel CPU Core2Duo E8400 2x 3.0Ghz w/2GB RAM, HDD 80GB Windows® XP embedded, integrated UPS • touch screen color monitor w/USB keyboard
Detector	1.2mm pitch or .8mm pitch, single energy
X-ray converter	16bit A/D Converter

Communications

I/O	I/O board with up to four input signals, four reject outputs, five PLC status signals, RS-232 interface
Network	Network card 10/100 mbps
Statistical data	Throughput, reject, weight, and system validation statistics available both in the GUI and SQL Database

Installation Data

X-ray leakage	Meets all applicable laws and regulations with respect to X-ray emitting devices including compliance with 21 CFR 1020.40 and 21 CFR 179.21
Protection rating/Operating temp	IP65/0°-43°C [32°-110°F]
Cooling method	4000 BTU/hr air conditioner
Power requirements	230 VAC, +15/-10%, 50/60 Hz, 20 Amp, single phase
Air requirements	5.5BAR [80psi], 9.5mm [3/8"] line, dry and filtered
Cabinet construction	Glass beaded stainless steel construction with conveyor bolted to cabinet
Conveyor belting	Seamless impregnated, polyester fiber underside with a white urethane top face coating, working temperature range of -30° to 100°C [-22° to 212°F]

Additional Features

Reject options	Signal only, reject light, single piston push arm, single lane air blast
Product guides	Available through tunnel and louvers
Multi-Task™	Software upgrade enabling advanced detection and control logic, discrete rejecting, reporting, and tracking capabilities
Reject stations	Multiple rejection stations linked to inspection routines

USA - Headquarters

3202 Regal Drive
Alcoa, TN 37701
T: +1 865 379 1670
F: +1 865 379 1677
E: sales@smithsdetection.com

United Kingdom

Unit 3, Odhams Trading Estate
Watford, Hertfordshire
WD24 7RY, UK
T: +44 (0) 1923 2944 00
F: +44 (0) 1923 2944 01

Singapore

100 Beach Road
#20-06 Shaw Towers
Singapore 189702
T: +65 (0) 6466 1700
F: +65 (0) 6469 2506

Mexico

Bldv. Luis Donaldo Colosio Km. 4.5
Las Palomas; Mineral de La
Reforma, Hidalgo, Mexico 42186
T: +52 (0) 7711 5329 29
F: +52 (0) 7711 5329 28

